



CERTIFICATE

No. A/13-304477

Rev 00

Date 2013-01-08

Page 1/2

INSPECTION CERTIFICATE acc to
EN 10 204 3.1

Processkontroll Items AB
Box 2088
444 02 STORA HÖGA
SWEDEN

INSPECTION STAMP
QA-TUBE

Customer References		Sandvik References		
712244	Customer order 2012-12-17	Order No. 315387	Subs No. 540838	ABSMT Dispatch note 38091/54
003-00991	ITEMS	ABSMT No. 300-77889	C.Code 15	

Material description SEAMLESS STAINLESS COLD FINISHED HYDRAULIC TUBING	Steel/material Designations Sandvik 3R60 EN no 1.4435
Steel making process Electric furnace	AISI TP316/TP316L

Technical requirements
 ASTM A-213-10A AW, ASME SA-213-ED-10 AD-11A AW, ASTM A-269-10
 NACE MR0175/ISO 15156-3:2009
 PED 97/23/EC EN 10216-5 TC1
 HRB MAX 80

EXTENT OF DELIVERY

It	Product designation	Heat	Lot	Pieces	Kg	M
01	THT-3R60-8-1.5 8.00 X 1.50	534193	51548	45	63.0	270.00
				Total	45	63.0 270.00

TEST RESULTS
Chemical composition (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
534193	0.019	0.45	1.54	0.028	0.010	17.25	13.11	2.52
	N							
534193	0.043							

Chemical composition, product (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
534193	0.021	0.43	1.55	0.029	0.008	17.26	13.10	2.53
	N							
534193	0.041							

Tensile test at room temperature

Lot	Yield strength		Tensile strength		Elongation	
	MPa	MPa	MPa		%	%
	Rp0.2	Rp1.0	Rm		A	4D
51548	299	345	575		54	55

Quality assurance - Per Eriksson / QA-manager
MTC Service / Certificates

**Hardness test**

	Min	Max
Lot	HRB	HRB
51548	70	72

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E
- Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at min 1040° C.

Marking:

SANDVIK 3R60 ASTM/ASME A/SA-213AW A-269 EN 10216-5 TC1 EN 10305-1 EN 1.4435 TP 316/316L COLD SMLS NDE 8.00 X 1.50 MM HT 534193 SS LOT 51548 MADE BY SANDVIK I N SWEDEN *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (97/23/EC) by TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.

The delivered products comply with the specifications and requirements of the order.

The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.

The certificate is produced with EDP and valid without signature.