

**CERTIFICATE****No. A/14-437481****Rev 00****Date 2014-08-15****Page 1/2**INSPECTION CERTIFICATE acc to
EN 10 204 3.1Processkontroll Items AB
Box 2088
444 02 STORA HÖGA
SWEDENINSPECTION STAMP
QA-TUBE

Customer References		Sandvik References	
750758	Customer order 2014-08-15	Order No. 378933	Subs No. 576510
003-00991	ITEMS	ABSMT No. 300-17790	Dispatch note 29001/54
		C.Code	

Material description	Steel/material Designations
SEAMLESS STAINLESS COLD FINISHED INSTRUMENTATION TUBING	Sandvik AISI 3R60 TP316/TP316L EN no 1.4435
Steel making process Electric furnace	

Technical requirements
ASTM A-213-13 AW, ASME SA-213-ED-10 AD-11A AW, ASTM A-269-13 NACE MR0175/ISO 15156-3:2009 PED 97/23/EC EN 10216-5 TC1 HRB MAX 80

EXTENT OF DELIVERY						
It	Product designation	Heat	Lot	Pieces	Kg	M
02	THT-3R60-19.05-1.24	539617	30058	4	13.0	24.00
	19.05 X 1.24					
Total				4	13.0	24.00
TEST RESULTS						
Chemical composition (weight%)						
Heat	C	Si	Mn	P	S	Cr
539617	0.018	0.36	1.62	0.030	0.009	17.30
	N					
539617	0.041					
Chemical composition, product (weight%)						
Heat	C	Si	Mn	P	S	Cr
539617	0.019	0.40	1.62	0.031	0.008	17.34
	N					
539617	0.043					
Quality assurance - Lars-Åke Bergqvist / QA-manager						
MTC Service / Certificates						

**Tensile test at room temperature**

	Yield strength		Tensile strength	Elongation	
	MPa	MPa	MPa	%	%
Lot	Rp0.2	Rp1.0	Rm	A	2"
30058	332	374	592	51	51
	332	374	595	50	48

Hardness test

	Min	Max
Lot	HRB	HRB
30058	78	80

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E
- Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at a temperature of Min 1040° C and quenched.

Marking:

SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4 435 TP316/316L CFA SMLS NDE 19.05 X 1.24 MM 3/4" X 18 BWG/SWG HT 539617 SS LO T 30058 MADE BY SANDVIK IN SWEDEN *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (97/23/EC) by TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.

The delivered products comply with the specifications and requirements of the order.

The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.

No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of AB Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.

The certificate is produced with EDP and valid without signature.