

CERTIFICATE

No. A/15-505750

Date 2015-06-09 Page 1/2

Rev 00

INSPECTION CERTIFICATE acc to EN 10 204 3.1

Processkontroll Items AB Box 2088

444 02 STORA HÖGA

SWEDEN

INSPECTION STAMP QA-TUBE

Customer References

Customer

order

2015-06-09

003-00991 ITEMS

751980

Sandvik References

Order No. Subs No. ABSMT Dispatch note

407772 592137 48455/54

ABSMT No. C.Code

300-31061 15

Material description

SEAMLESS STAINLESS COLD FINISHED

HYDRAULIC TUBING

Steel/material Designations

Sandvik AISI

3R60 TP316/TP316L

EN no 1.4435

Steel making process

Electric furnace

Technical requirements

ASTM A-213-13 AW, ASME SA-213-ED-13 AW, ASTM A-269-13

NACE MR0175/ISO 15156-3:2009

PED 97/23/EC EN 10216-5 TC1

HRB MAX 80

EXTENT OF DELIVERY

 It Product designation
 Heat Lot Pieces
 Kg
 M

 01 THT-3R60-6-1
 048115 40477 80 60.0 480.00

6.00 X 1.00

Total 80 60.0 480.00

KEY TO HEAT

Heat Code Heat No.

048115 540236

TEST RESULTS

Chemical composition (weight%)

Heat C Si Mn \mathtt{Cr} Νi Mo Ρ S 0.031 0.0080 17.21 048115 0.022 0.35 1.63 13.00 2.53

N

048115 0.041

Chemical composition, product (weight%)

 Heat
 C
 Si
 Mn
 P
 S
 Cr
 Ni
 Mo

 048115
 0.026
 0.36
 1.63
 0.030
 0.0060
 17.28
 13.00
 2.54

048115 0.026 0.36 1.63 0

048115 0.040

Quality assurance - Lars-Åke Bergqvist / QA-manager MTC Service / Certificates



CERTIFICATE

No. A/15-505750

Date

Rev 00 2015-06-09 Page 2/2

Tensile test at room temperature

Yield strength Tensile strength Elongation MPa MPAMPa % Rp0.2 Rp1.0 Rm4D Α 299 348 580 54 51

Hardness test

Lot

40477

Max Min HRB HRB Lot 40477 72 74

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E
- Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at a temperature of Min 1040° C and quenched.

Marking:

SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4 435 TP316/316L CFA SMLS NDE 6.00 X 1.00 MM HT 540236 SS LOT 40477 MADE BY SAND VIK IN SWEDEN *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (97/23/EC) by TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.

The delivered products comply with the specifications and requirements of the order.

The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.

No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of AB Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.

The certificate is produced with EDP and valid without signature.