



CERTIFICATE

No. A/15-473509

Rev 00

Date 2015-01-23

Page 1/2

INSPECTION CERTIFICATE acc to
EN 10 204 3.1

Processkontroll Items AB
Box 2088
444 02 STORA HÖGA
SWEDEN

INSPECTION STAMP
QA-TUBE

Customer References		Sandvik References		
751443	Customer order 2015-01-23	Order No. 394047	Subs No. 584809	ABSMT Dispatch note 39565/54
003-00991	ITEMS	ABSMT No. 300-24741	C.Code 15	

Material description SEAMLESS STAINLESS COLD FINISHED HYDRAULIC TUBING	Steel/material Designations Sandvik 3R60 EN no 1.4435
Steel making process Electric furnace	AISI TP316/TP316L

Technical requirements
 ASTM A-213-13 AW, ASME SA-213-ED-10 AD-11A AW, ASTM A-269-13
 NACE MR0175/ISO 15156-3:2009
 PED 97/23/EC EN 10216-5 TC1
 HRB MAX 80

EXTENT OF DELIVERY

It	Product designation	Heat	Lot	Pieces	Kg	M
01	THT-3R60-8-1 8.00 X 1.00	540763	35479	10	10.0	60.00
				Total	10	60.00

TEST RESULTS
Chemical composition (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
540763	0.020	0.43	1.76	0.030	0.007	17.17	13.03	2.52
	N							
540763	0.037							

Chemical composition, product (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
540763	0.020	0.42	1.74	0.030	0.007	17.22	13.04	2.52
	N							
540763	0.043							

Tensile test at room temperature

Lot	Yield strength		Tensile strength		Elongation	
	MPa	MPa	MPa		%	%
	MPa	MPa	MPa		%	%
	Rp0.2	Rp1.0	Rm		A	4D
35479	278	326	561		54	51

Quality assurance - Lars-Åke Bergqvist / QA-manager
MTC Service / Certificates

**Hardness test**

	Min	Max
Lot	HRB	HRB
35479	72	74

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E
- Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at a temperature of Min 1040° C and quenched.

Marking:

SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD EN 1.4435
TP316/316L CFA SMLS NDE 8.00 X 1.00 MM HT 540763 SS LOT 35479 MADE BY SANDVIK
IN SWEDEN *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to
Pressure Equipment Directive (97/23/EC) by
TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot
before cutting to finished lengths.

The delivered products comply with the specifications and
requirements of the order.

The material is manufactured according to a Quality system,
approved and registered to ISO 9001:2008.

No unauthorized alterations. The contents of this Inspection
Certificate may not be modified or revised in any way without the
prior written approval of AB Sandvik Materials Technology.
Unauthorized alterations to the Inspection Certificate, including
introduction of false, fictitious or fraudulent statements or entries,
may be punishable by fines, imprisonment, or both. This Inspection
Certificate may be copied only in the manner and for the purposes
specified in Section 6 of EN 10204:2004. Contravention of this notice
will be prosecuted to the fullest extent of applicable law.

The certificate is produced with EDP and valid without signature.