

INSPECTION CERTIFICATE acc to Processkontroll Items AB EN 10 204 3.1

Box 2088 444 02 STORA HÖGA SWEDEN

INSPECTION STAMP QA-TUBE

Customer References		Sandvik Re	eferences					
	Customer	Order No.	Subs No.	ABSMT 1	Dispatch n	ote		
752490	order	420303	598589	07240/	54			
	2015-10-16	ABSMT No.						
		300-36882	15					
003-00991 ITEMS								
Material description SEAMLESS STAINLESS COLD	TNICUED	Steel/mate Sandvik	erial Desig	gnation: AISI	S			
HYDRAULIC TUBING	LINIQUED	3R60			/TP316L			
		EN no		IF JIO,	/IEJIOH			
		1.4435						
Steel making process								
Electric furnace								
Technical requirements			0.60 1.0					
ASTM A-213-15A AW, ASME		AW, ASTM A	A-269-13					
NACE MR0175/ISO 15156-3: PED 97/23/EC EN 10216-5								
HRB MAX 80	ICI							
IRD MAX OU								
EXTENT OF DELIVERY								
It Product designa	tion Hea	t Lot I	Pieces	Kg	м			
01 THT-3R60-6-1		152 46144	30	23.0	180.00			
6.00 X 1.00								
			20	0.2 0	100 00			
KEY TO HEAT		Total	30	23.0	180.00			
Heat Code Heat No.								
048152 541031								
TEST RESULTS								
Chemical composition (we	eight%)							
Heat C Si	Mn		S C:		Ni	Mo		
048152 0.019 0.37	1.58	0.030 0.	.0090 17.	25 1	3.11 2	2.54		
N								
048152 0.039								
		+ 0.)						
Chemical composition, pr				~	NT -	Me		
Heat C Si 048152 0.022 0.38	Mn 1.58		5 	r 26 1'		Mo 2.54		
N	1.00	0.031 0.	.0090 I/.	20 I.	5.00 2	. 94		
N 048152 0.042								
Quality assurance -								
MTC Service / Certificates								

AB SANDVIK MATERIALS TECHNOLOGY Reg No. 556234-6832 VAT No. SE663000-060901 SE-81181 SANDVIKEN SWEDEN www.smt.sandvik.com mtc_service.smt@sandvik.com



Tensile test at room temperature							
	Yield MPA	strength MPa	Tensile strength MPa	Elongation %%			
Lot		Rp1.0	Rm	а 2"			
46144	337	381	583	56 53			
Hardness tes	+						
	Min	Max					
Lot 46144	HRB 74	HRB 75					
40144	74						
<pre>Following controls/tests have been satisfactorily performed: - 100% Flattening test acc to EN ISO 8492 Flaring test - PMI-test Intergranular corrosion test acc to ASTM A-262 PR.E - Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016 Visual inspection and dimensional control.</pre>							
Heat Treatment: Solution annealed at a temperature of Min 1040° C and quenched.							
Marking: SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4 435 TP316/316L CFA SMLS NDE 6.00 X 1.00 MM HT 541031 SS LOT 46144 MADE BY SAND VIK IN SWEDEN *QA-TUBE*							
The raw material is free from radioactive contamination.							
Material free from mercury contamination.							
Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (97/23/EC) by TUEV NORD; notified body, reg.no. 0045.							
The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.							
The delivered products comply with the specifications and requirements of the order.							
The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.							
No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of AB Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.							
The certificate is produced with EDP and valid without signature.							