

INSPECTION CERTIFICATE acc to Processkontroll Items AB EN 10 204 3.1

Box 2088 444 02 STORA HÖGA SWEDEN

INSPECTION STAMP QA-TUBE

Customer References		Sandvik References			
	Customer	Order No.	Subs No.	ABSMT Dispatch note	
752740	order	425832	601589	10770/54	
	2015-12-09	ABSMT No.	C.Code		
		300-39386	15		
003-00991 ITEMS					
Material description		Steel/mater	rial Desig	quations	
SEAMLESS STAINLESS COLD	FINISHED	Sandvik	-	AISI	
HYDRAULIC TUBING		3R60		TP316/TP316L	
		EN no			
		1.4435			
Steel making process					
Electric furnace					
Technical requirements ASTM A-213-15A AW, ASME	כו היה כור גים		260 14		
		AW, ASIM A	-209-14		
NACE MR0175/ISO 15156-3:					
PED 97/23/EC EN 10216-5	TCT				
HRB MAX 80					
EXTENT OF DELIVERY					
It Product designa	tion Hea	t Lot P:	ieces	Kg M	

01 '		<b>ct designat</b> 50-10-1.5 K 1.50		<b>Heat</b> 048190	<b>Lot</b> 48903	Pieces 5	<b>Kg</b> 10.		<b>M</b> 0.00
					Total	5	10.	0 3	0.00
KEY TO H	EAT								
Heat Cod 048190	e	<b>Heat No.</b> 542663							
TEST RES	ULTS								
Chemical	compos	sition (wei	ght%)						
Heat	C	Si	Mn	Р		S	Cr	Ni	Mo
048190	0.020	0.39	1.55	0.03	32 (	0.0080	17.26	13.36	2.53
	N								
048190	0.034								
Chemical composition, product (weight%)									
Heat	C	Si	Mn	Р		S	Cr	Ni	Mo
048190	0.019	0.41	1.55	0.03	31 (	0.0070	17.25	13.33	2.53
048190	<b>N</b> 0.040								
Quality assurance – Lars-Åke Bergqvist / QA-manager MTC Service / Certificates									

MTC Service / CertificatesAB SANDVIK MATERIALS TECHNOLOGY Reg No. 556234-6832 VAT No. SE663000-060901 SE-81181 SANDVIKEN SWEDEN www.smt.sandvik.com mtc\_service.smt@sandvik.com



Tensile test		temperature	Tongila strongth	Flongation		
	Y1eld MPA	strength MPa	Tensile strength MPa	Elongation % %		
Lot		Rp1.0	Rm	A 4D		
48903	291	331	555	52 51		
Hardness tes	÷					
naroness ces	Min	Max				
Lot	HRB	HRB				
48903	74	76				
<pre>Following controls/tests have been satisfactorily performed: Flattening test. Flaring test PMI-test. Intergranular corrosion test acc to ASTM A-262 PR.E Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016. Visual inspection and dimensional control.</pre>						
Heat Treatme Solution ann		a temperatur	e of Min 1040° C and	d quenched.		
Marking: SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4 435 TP316/316L CFA SMLS NDE 10.00 X 1.50 MM HT 542663 SS LOT 48903 MADE BY SAN DVIK IN SWEDEN *QA-TUBE*						
The raw material is free from radioactive contamination.						
Material free from mercury contamination.						
Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (97/23/EC) by TUEV NORD; notified body, reg.no. 0045.						
The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.						
The delivered products comply with the specifications and requirements of the order.						
The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.						
No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of AB Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.						
The certificate is produced with EDP and valid without signature.						