



CERTIFICATE

No. A/16-561597 Rev 00
Date 2016-03-03 Page 1/2

INSPECTION CERTIFICATE acc to
EN 10204 3.1

Processkontroll Items AB
Box 2088
444 02 STORA HÖGA
SWEDEN

INSPECTION STAMP
QA-TUBE

Customer References		Sandvik References	
753127	Customer order 2016-03-03	Order No. 433785	Subs No. 606002
003-00991	ITEMS	ABSMT No. 300-43136	Dispatch note 16105/54
		C.Code 15	

Material description SEAMLESS STAINLESS COLD FINISHED HYDRAULIC TUBING	Steel/material Designations Sandvik AISI 3R60 TP316/TP316L EN no 1.4435
Steel making process Electric furnace	

Technical requirements
 ASTM A-213-15C AW, ASME SA-213-ED-15 AW, ASTM A-269-15A
 NACE MR0175/ISO 15156-3:2009
 PED 97/23/EC EN 10216-5 TC1
 HRB MAX 80

EXTENT OF DELIVERY

It	Product designation	Heat	Lot	Pieces	Kg	M
01	THT-3R60-8-1 8.00 X 1.00	048212	53028	20	21.0	120.00
				Total	20	21.0 120.00

KEY TO HEAT

Heat Code	Heat No.
048212	543416

TEST RESULTS

Chemical composition (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
048212	0.020	0.42	1.65	0.031	0.0080	17.32	13.32	2.52
	N							
048212	0.039							

Chemical composition, product (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
048212	0.020	0.43	1.65	0.032	0.0050	17.36	13.32	2.52
	N							
048212	0.041							

Quality assurance - Lars-Åke Bergqvist / QA-manager
MTC Service / Certificates

**Tensile test at room temperature**

Lot	Yield strength		Tensile strength	Elongation	
	MPa	MPa	MPa	%	%
	Rp0.2	Rp1.0	Rm	A	4D
53028	328	369	592	49	46

Hardness test

Lot	Min	Max
	HRB	HRB
53028	73	75

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E
- Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at a temperature of Min 1040° C and quenched.

Marking:

SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4
435 TP316/316L CFA SMLS NDE 8.00 X 1.00 MM HT 543416 SS LOT 53028 MADE BY SAND
VIK IN SWEDEN *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to
Pressure Equipment Directive (97/23/EC) by
TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot
before cutting to finished lengths.

The delivered products comply with the specifications and
requirements of the order.

The material is manufactured according to a Quality system,
approved and registered to ISO 9001:2008.

No unauthorized alterations. The contents of this Inspection
Certificate may not be modified or revised in any way without the
prior written approval of AB Sandvik Materials Technology.
Unauthorized alterations to the Inspection Certificate, including
introduction of false, fictitious or fraudulent statements or entries,
may be punishable by fines, imprisonment, or both. This Inspection
Certificate may be copied only in the manner and for the purposes
specified in Section 6 of EN 10204:2004. Contravention of this notice
will be prosecuted to the fullest extent of applicable law.

The certificate is produced with EDP and valid without signature.