

INSPECTION CERTIFICATE acc to Processkontroll Items AB EN 10204 3.1

Box 2088 444 02 STORA HÖGA SWEDEN

INSPECTION STAMP QA-TUBE

Customer References	Sandvik References				
753429	Customer order 2016-05-18		Subs No. 610256 C.Code	ABSMT Dispatch note 21380/54	
003-00991 ITEMS					
Material description		Steel/mater	rial Desi	qnations	
SEAMLESS STAINLESS COLD	FINISHED	Sandvik		AISI	
HYDRAULIC TUBING		3R60		TP316/TP316L	
		EN no			
		1.4435			
Steel making process					
Electric furnace					
Technical requirements					
ASTM A-213-15C AW, ASME SA-213-ED-15 AW, ASTM A-269-15A					

NACE MR0175/ISO 15156-3:2015, NACE MR0103/ISO 17495:2015 PED 97/23/EC EN 10216-5 TC1 HRB MAX 80

	F DELIVE					_			
		designa		Heat	Lot		5		1
	THT-3R60			048237	55954	10	10.0	60.	.00
	8.00 X 1	.00							
					Total	10	10.0	60.	.00
КЕҮ ТО Н	EAT								
Heat Cod	e H	eat No.							
048237	5	43864							
TEST RES	ULTS								
Chemical	composi	tion (we	ight%)						
Heat	C	Si	Mn	Р		S	Cr	Ni	Mo
048237	0.020	0.37	1.61	0.03	31	0.0120	17.26	13.02	2.53
	N								
048237	0.036								
Chemical composition, product (weight%)									
Heat	C	Si	Mn	P		S	Cr	Ni	Мо
048237	0.018	0.37	1.60	0.03	30	0.0120	17.27	13.01	2.50
	N								
048237	0.035								

Quality assurance - Lars-Ake Bergqvist / QA-manager MTC Service / Certificates

AB SANDVIK MATERIALS TECHNOLOGY Reg No. 556234-6832 VAT No. SE663000-060901 SE-81181 SANDVIKEN SWEDEN www.smt.sandvik.com mtc\_service.smt@sandvik.com



Tensile tes	t at room	temperature	9		
	Yield a	strength	Tensile strength	-	
	MPA	MPa	MPa	% % - 1-	
<b>Lot</b> 55954	<b>Rp0.2</b> 303	<b>Rp1.0</b>	<b>Rm</b> 564	<b>A 4D</b> 50 52	
55954	303	222	504	50 52	
Hardness te	st				
	Min	Max			
Lot	HRB	HRB			
55954	73	75			
<pre>Following controls/tests have been satisfactorily performed: - Flattening test Flaring test - PMI-test Intergranular corrosion test acc to ASTM A-262 PR.E - Leak test: Eddy current test acc to EN ISO 10893-1, ASME SA-1016 Visual inspection and dimensional control.</pre>					
Heat Treatment: Solution annealed at a temperature of Min 1040° C and quenched.					
Marking: SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4 435 TP316/316L CFA SMLS NDE 8.00 X 1.00 MM HT 543864 SS LOT 55954 MADE BY SAND VIK IN SWEDEN *QA-TUBE*					
The raw material is free from radioactive contamination.					
Material free from mercury contamination.					
Approved ac Pressure Eq TUEV NORD;	uipment D:	irective (97		. to	
The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.					
The deliver requirement	-		th the specification	s and	
The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.					
No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of AB Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.					
The certificate is produced with EDP and valid without signature.					