

INSPECTION CERTIFICATE acc to EN 10204 3.1

Processkontroll Items AB Box 2088 444 02 STORA HÖGA SWEDEN

INSPECTION STAMP QA-TUBE

Quatomon Defemended		Sandvik References				
Customer References 753509 003-00991 ITEMS	Customer order 2016-06-03		Subs No. 611298 C.Code	ABSMT Dispatch note 22574/54		
Material description SEAMLESS STAINLESS COLD : HYDRAULIC TUBING	FINISHED	Steel/mate Sandvik 3R60 EN no 1.4435	rial Desig	<b>gnations</b> AISI TP316/TP316L		
Steel making process Electric furnace Technical requirements						

ASTM A-213-15C AW, ASME SA-213-ED-15 AW, ASTM A-269-15A NACE MR0175/ISO 15156-3:2015, NACE MR0103/ISO 17495:2015 PED 97/23/EC EN 10216-5 TC1 HRB MAX 80

EXTENT OF DELIVERY									
It Product designation			Heat Lot Piec			-	M		
01 THT-3R60-12-1.5			048242 56175		5	12.0		30.00	
12.00 X 1.50									
					Total	5	12.0	30.	00
KEY TO H	EAT								
Heat Code	e 1	Heat No.							
048242	!	544140							
TEST RESULTS									
Chemical	compos	ition (wei	.ght%)						
Heat	С	Si	Mn	Р		S	Cr	Ni	Mo
048242	0.021	0.39	1.59	0.03	30	0.0090	17.28	13.05	2.53
	N								
048242	0.041								
Chemical composition, product (weight%)									
Heat	с	Si	Mn	P		S	Cr	Ni	Mo
048242	0.023	0.40	1.61	0.03	31	0.0080	17.28	13.02	2.51
	N								
048242	0.041								
Quality assurance – Lars-Åke Bergqvist / QA-manager MTC Service / Certificates									

AB SANDVIK MATERIALS TECHNOLOGY Reg No. 556234-6832 VAT No. SE663000-060901 SE-81181 SANDVIKEN SWEDEN www.smt.sandvik.com mtc\_service.smt@sandvik.com



Tensile test		temperature strength MPa	Tensile strength MPa	Elongation %%				
<b>Lot</b> 56175	<b>Rp0.2</b> 273	<b>Rp1.0</b> 307	<b>Rm</b> 568	<b>A 2"</b> 62 59				
Hardness test				00				
	Min	Max						
<b>Lot</b> 56175	<b>HRB</b> 70	<b>HRB</b> 73						
<pre>Following controls/tests have been satisfactorily performed: - Flattening test Flaring test - PMI-test Intergranular corrosion test acc to ASTM A-262 PR.E - Leak test: Eddy current test acc to EN ISO 10893-1, ASME SA-1016 Visual inspection and dimensional control.</pre>								
Heat Treatment: Solution annealed at a temperature of Min 1040° C and quenched.								
Marking: SANDVIK 3R60 ASTM/ASME A/SA-213 A-269 EN 10216-5 TC1 EN 10305-1 COLD AW EN 1.4 435 TP316/316L CFA SMLS NDE 12.00 X 1.50 MM HT 544140 SS LOT 56175 MADE BY SAN DVIK IN SWEDEN *QA-TUBE*								
The raw material is free from radioactive contamination.								
Material free	from m	ercury contam	ination.					
Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (97/23/EC) by TUEV NORD; notified body, reg.no. 0045.								
The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.								
The delivered products comply with the specifications and requirements of the order.								
The material is manufactured according to a Quality system, approved and registered to ISO 9001:2008.								
No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of AB Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.								
The certificate is produced with EDP and valid without signature.								